




35 X

Total flexibility, unmatched performance, premium reliability.





PERFORMANCE SPECIFICATIONS



Condenser

Dimensions:
44.3" x 22.7" x 9.3"
(1,125 x 577 x 236 mm)



Evaporator

Dimensions:
42.5" x 24" x 7.75"
(1,080 x 610 x 197 mm)

Cab Command Cab Command™2

Dimensions:
3.4" x 2.4" x 1.1"
(85 x 60 x 28 mm)



Cab Command™2 shown here

Cooling/Temperature Capacity:
Ambient at 100°F (38°C)
Compressor Speed: 2,400 rpm @ 60 Hertz

Evaporator Return Air Temp.	Road BTU/hr (Watts)	Standby BTU/hr (Watts)
35°F (2°C)	10,500 (3,077)	6,700 (1,964)
0°F (-18°C)	6,300 (1,846)	3,000 (879)

Standard Features Include:

- Durable composite skin
- Extra-flat SlimLine™ evaporator
- 9 CID (147 cc) six-cylinder swash plate compressor
- Poly-V groove clutch
- Refrigerant – R-404A
- Brushless evaporator fan motors
- Hot gas defrost
- Hot gas heating
- Condenser valve enhanced heating circuit
- Refrigerant injector
- Integrated oil separator
- Low refrigerant pressure protection
- High refrigerant pressure protection
- Microprocessor control system
- Cab Command™2
 - Red light visual warning (in cab)
 - Main On/Off system power keys
 - Timed defrost interval
 - Manual defrost key
 - Diagnostic safety indicators
 - Adjustable minimum/maximum setpoint configuration
- Digital readout
 - Cab Command (in cab)
 - Adjustable display brightness
 - Current and stored alarms (Note: when Road Only, the Cab Command will have a 3-digit screen)
- Automatic defrost control
 - Programmable defrost timer
 - Automatic defrost termination
 - Manual defrost override

Accessories and Options:

- Electric Standby
 - 115v - 1ph-60Hz
 - 208/230v - 3ph - 60Hz
 - 208/230v - 1ph - 60Hz
- Double-A groove clutch
- Variable groove clutch
- Rear port adapter
- Roofmount installation kit

Approximate Weights:

- Condenser Weights:
 - 143 lb (65 kg) engine operation only
 - 207 lb (94 kg) stand by
- Evaporator Weight:
 - 64 lb (29 kg)

Specifications are subject to change without notice.
Warranty: Product warranty and limitations are outlined in Form 62-03703.
This warranty applicable only in North America. Consult your Carrier Transcold representative for warranty coverage elsewhere. Form 62-12030 Rev A.

North America
Carrier Transcold
700 Olympic Drive
Athens, GA 30601 USA

Central America and Mexico
Carrier Transcold
Ejercito Nacional 253-A Piso 5
Colonia Anahuac
11320 Mexico D.F.

